

## BUILT FOR PURPOSE

### DALLAS 30W BACKLIT PANEL



After listening to feedback from our customers and contractors, we have developed a new lower lumen **DALLAS 30W** backlit panel to provide subtle illumination. The new **DALLAS** panel is available in 4000K offering moderate illumination in comparison to our existing **DALLAS** panels. The panel features a low UGR rating of <19 making it an ideal solution for office and educational settings. This panel features a TP(a) rated diffuser ensuring they can be used without restrictions. It is 600x600mm and fits into standard size ceiling grids so can be retrofitted easily and with an extremely high efficacy of 109lm/w there has never been a better reason to upgrade to the ROBUS **DALLAS 30W** panel.

#### KEY FEATURES

- Suitable for use in offices, shops, reception areas, restaurants, hotels, schools, hospitals
- Low glare rating of UGR<19
- TP(a) rated diffuser in accordance with BS2782.0:2011 Method 508A
- LED replacement for 4x18W T8 lay-in modular
- Fits into standard sizes of ceiling grid - 15mm and 24mm
- Wide operating ambient temperature range of -20°C to +40°C
- 50,000-hour average lamp life. Up to 5 times that of a standard fluorescent lamp
- Very high efficacy of 109lm/W
- Suitable for switching by PIR, Microwave or Photocell



CODE	DESCRIPTION
RDL3040-01	DALLAS 30W UGR LED backlit Panel,600x600mm, TP(a) White,4000K

IF YOU WOULD LIKE MORE INFORMATION ON THIS PRODUCTS PLEASE CONTACT YOUR LOCAL ROBUS AREA SALES MANAGER OR CALL 01 709 9000 (FROM IRELAND), 0800 973 220 (FREEPHONE FROM UK), +353 1 7099000 (INTERNATIONAL PHONE NUMBER).